



Plant-mimetic heat pipes for operation with large inertial and gravitational stresses

Abraham Stroock

School of Chemical and Biomolecular Engineering
Kavli Institute at Cornell for Nanoscale Science and Technology
Cornell University

N. Michelle Holbrook and Maciej Zwieniecki

Department of Organismic and Evolutionary Biology
Harvard University


AFOSR - #FA9550-09-1-0188 (B.L. Lee, PM)


Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE AUG 2012		2. REPORT TYPE		3. DATES COVE 00-00-2012	red to 00-00-2012
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
Plant-mimetic heat pipes for operation with large inertial and gravitational stresses				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Cornell University, School of Chemical and Biomolecular Engineering, Kavli Institute at Cornell for Nanoscale Science and Technology, Ithaca, NY, 14853 8. PERFORMING ORGANIZATION REPORT NUMBER					
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at the 2nd Multifunctional Materials for Defense Workshop in conjunction with the 2012 Annual Grantees'/Contractors' Meeting for AFOSR Program on Mechanics of Multifunctional Materials & Microsystems Held 30 July - 3 August 2012 in Arlington, VA. Sponsored by AFRL, AFOSR, ARO, NRL, ONR, and ARL. U.S. Government or Federal Rights License					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFIC	17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	43	RESPONSIBLE PERSON

Report Documentation Page

Form Approved OMB No. 0704-0188

Problem – efficient heat transfer





heat flux:

 $J \rightarrow 100 \text{ W/cm}^2$

temperature:

 $T_{\text{source}} \leq 100 \, ^{\circ}\text{C}$

$$\Delta T_{\min} = 60 \, ^{\circ}C$$




temperature:

 $T_{sink} \le 40$ °C

Conduction:

$$L = \frac{k\Delta T}{J} = 2.4 \text{ cm}$$




Convection:


$$Q = \frac{J}{\rho C_{\rho} \Delta T} = 0.4 \frac{\text{mL/s}}{\text{cm}^2}$$

Phase change:

$$Q = \frac{J}{\rho \lambda} = 0.04 \; \frac{\text{mL/s}}{\text{cm}^2}$$



Heat pipes - closed loop phase change








- autonomous (no pump)
- self-contained
- near-isothermal operation

Limitations

- capillary limit
 - \Rightarrow short (~1 m), low load (\leq 1 g)
- entrainment limit
 - ⇒ limited heat flow







www.microloops.com


$$r_{p} \ge 1 \, \mu \text{m}$$


$$\Delta P \le \frac{2\gamma}{r_p} \le 1 \text{ bar}$$

Goal: Efficient heat transfer

- over long distances (10 m)
- with adverse gravitational and inertial loads (up to 10 g)

Opportunity – large stresses from small pores






$$r_p < 10 \, \text{nm}$$

$$P_{vap} - P_{liq} = \frac{2\gamma}{r_p} >> 1 \text{ bar}$$


 $\Rightarrow P_{liq} = P_{vap} - \frac{2\gamma}{r_p} << 0$

$$\Rightarrow P_{liq} = P_{vap} - \frac{2\gamma}{r_p} << 0$$

- ⇒ Negative pressure
- ⇒ Metastable (superheated)



Opportunity – large stresses from small pores



Effective Thermal Resistance:

$$\mathcal{R}_{total} = \mathcal{R}_{liq} + \mathcal{R}_{vap} + \mathcal{R}_{wall}$$

$$0.3$$

$$0.1 \quad \mathcal{R}_{vap}$$

$$0.1 \quad \mathcal{R}_{vap}$$

$$\mathcal{R}_{liq}$$

$$300 \quad 310 \quad 320 \quad 330 \quad 340 \quad 350 \quad 360$$

$$\mathbf{condenser\ temp., T_0} [K]$$


 Impact of viscous and inertial stresses negligible.

$$\Rightarrow$$
 R_{total} \sim R_{wall}

⇒ total resistance ~ 3 mm of copper

(Chen et al., submitted, 2012)

Challenge – large stresses from small pores



Effective Thermal Resistance:

$$\mathcal{R}_{total} = \mathcal{R}_{liq} + \mathcal{R}_{vap} + \mathcal{R}_{wall}$$

$$0.3 \quad \mathcal{R}_{total}$$

$$0.1 \quad \mathcal{R}_{vap} \quad \mathcal{R}_{wall}$$

$$\mathcal{R}_{liq}$$


$$300 \quad 310 \quad 320 \quad 330 \quad 340 \quad 350 \quad 360$$

$$condenser temp., T_0 [K]$$

- $P_{lig} \sim -20$ bars for q = 10 W/cm²
- additional -1 bar per W/cm²
- ⇒ must manage metastability

(Chen et al., submitted, 2012)

Challenge – but plants do it every day...



Synthetic trees - negative pressure wicks

"soil": (liquid) "atm": (vapor)

$$a_s = 1$$


 $a_a = 0.75$


$$P = P_0$$

 $P = P_0$

$$T = 25^{\circ}$$


 $T = 25^{\circ}$







$$\Psi_{\text{soil}} = 0 \text{ bar}$$

 $\Psi_{\text{soil}} = 0 \text{ bar}$ $\Psi_{\text{atm}} = -380 \text{ bar}$




Synthetic trees - negative pressure wicks





- catastrophic failure
- mechanical collapse
- low flux (large membrane resistance)

Managing tension











Managing tension – autonomic functions




1. Flow control – experiments

lauris nobilis (bay tree)



(Zwieniecki et al., Science, 2001)

various species



-40

- resistance ↓ with ionic strength ↑
- resistance ↓ with pH ↓

7.5

 H_2O

8000

7.5

KC

6000


4500

7.5


H₂O

4000


time (s)




(Cochard et al., J. Exp. Bot., 2009)




Hydrogel:







Hydrogel:




(Lee, Holbrook & Zwieniecki, Front. Plant Sci., 2012)


high ionic strength/low pH (collapsed)







Electroviscous effect:





Electroviscous effect:






(Cochard et al., J. Exp. Bot., 2009)

i. positive


ii. neutral


iii. negative

(Santiago et al., in preparation, 2012)



Electroviscous effect:






(Santiago et al., in preparation, 2012)


1. Flow control – precedent

Hydrogel:




(Beebe et al., Nature, 2000)

Electroviscous effect:



2. Refilling – experiments

Populus nigra (black poplar)



(Secchi and Zwieniecki, 2012)


2. Refilling – experiments

Acer rubrum (red maple); $P_{vessels} = -5$ bars

MRI (30 minutes)




2. Refilling – experiments




(Zwieniecki, Melcher, Ahrens & Holbrook, in revisions, 2012)

2. Refilling – mechanism?



2. Refilling – mechanism?




(Zwieniecki & Holbrook, Trends in Plant Sciences, 2009)

2. Refilling – molecular mechanisms


Differential gene expression after induced embolization

Populus trichocarpa (black cottonwood)




- ~9,000 genes differentially expressed after embolization
- Clues to biochemical and biophysical mechanisms
 i,ii) pore proteins ⇒ active and passive transport mechanisms
 iii) carbohydrate metabolism ⇒ source of deployable energy
 - iv) down regulation of genes for oxidative stress ⇒ possible trigger


Driving force for refilling?:




what's in this water?




activity =
$$a \le exp\left(\frac{\bar{v}(P_{xyl} - P_0)}{RT}\right)$$






Secret formula for water collection




osmolarity balances stress in rehydrated plant

(Secchi & Zwieniecki, Plant Physio, 2012)




2. Refilling – emerging picture



⇒ Not "dead wood"!

Synthetic tree – challenges



Material multifunctionality:

- high modulus
- high thermal conductivity
- integrated *nano-scale* and scale porosity

Integrated analysis:

- pressure, temperature, fluxes

Management of metastability:


- isolating cavitation (boiling) events
- repairing cavitated zones

Fundamental understanding:

 transport and thermodynamics of liquids at NP

Synthetic tree – version 2.0

Wicks for negative pressure heat pipes




Silicon MEMS platform

- → mechanical + thermal properties
- → integration of sensors (pressure, temperature, flux)

Composite structures


- → selective porosity
- → large stresses/large fluxes
- → failure isolation


Synthetic tree – version 2.0





Synthetic tree - root/leaf membranes:

root/leaf membranes:










⇒ 100% stability to -100 bars


Synthetic tree – integration




- long transients...
- embedding?


Synthetic trees – segmented xylem

segmented vessels







Synthetic trees – segmented xylem



Spatially isolated cavitation events


Synthetic trees - segmented xylem






τ (sec)


Synthetic trees – segmented xylem




- acoustic triggering?
- hydraulic suppression?




Synthetic trees - segmented xylem






- acoustic riggering?
- hydraulic suppression?
 - Acoustic signals, but not triggering additional events.
 - But, acoustic signatures = opportunity for autonomic response.


Synthetic tree - segmented xylem



- acoustic riggering?
- hydraulic suppression?

hydraulic suppression






$$\tau_{\text{hyd}}$$
 = 5.3 min $\cong \tau_{\text{corr}}$

Drying proceeds in "avalanches" with suppression by re-saturation.


Synthetic tree – segmented xylem

Physiology of "border pit membrane"?



Washburn eqn. for capillary wetting:


$$x(t) = \sqrt{\frac{\gamma d_{pore}t}{4\eta}}$$




- $d_{pore} = 0.35 \text{ nm}$
- consistent with $au_{ ext{hyd}}$


Conclusions

biomolecular insights




biophysical insights







integrated understanding



synthetic physiology








tools for integration





Acknowledgements

Grads:

Erik Huber (MAE)

I-Tzu Chen (CBE)

Michael Santiago (MAE)

Eugene Choi (CBE)

Vinay Pagay (Hort.)

Anthony Diaz (CBE)

Pavithra Sundararajan (MAE)

Vikram Singh (CBE)

John Morgan (CBE)

Alumni:

Tobias Wheeler (→ Caliper Inc.)

Joseph Kirtland (→ Dordt College)

Cecile Cottin-Bizonne (→ U. of Lyon)

Mario Cabodi (→ Boston U.)

Nakwon Choi (→ MIT/Novartis)

Valerie Cross (\rightarrow Gore Inc.)

Stephane Badaire (→ Michelin)

Ying Zheng (→ UW Med)

Amit Pharkya

Post-docs:

Scott Verbridge Michael Craven

David Sessoms

Rachel Liang

Collaborators

Frederic Caupin (Lyon)
Michelle Holbrook (Harvard)
Maciej Zwieniecki (Harvard)
Francesca Secchi (Harvard)
Alan Lakso (Cornell)

Funding:













